

Drake-Scruggs Equipment Inc.

Distributors of Truck and Utility Equipment

Home Office

2000 South Dirksen Parkway
P.O. Box 2549
Springfield, IL 62708-
(217) 753-3871
Fax (217) 753-2760

Branch Office

4101 W. Main Street
Grandview, MO 64030-
(816) 765-5525
Fax (816) 765-8522

****Call for current pricing****

Quote Number **010110-0**

Aerial Unit

Versalift VST-47-I, 46'-4", insulated, telescopic aerial platform lift with material handling capabilities.

- Hydraulic platform leveling.
- 8" x 10" rectangular outer boom with 9" x 11" fiberglass Electroguard section. Inner boom is 6-7/8" x 8-7/8" rectangular fiberglass housed within the outer boom.
- Non-lube bearings used at most points of motion. Only the rotation bearing requires periodic lubrication.
- Unrestricted continuous rotation.
- Open center hydraulic system, rated for 6 gpm at 3000 PSI.
- Telescopic upper boom featuring the patented "Electroguard" with fiberglass inner boom meeting ANSI A92.1990 requirements for category C, 46 KV and below, fully retracted.
- Lower boom insert providing 12" insulation gap that meets ANSI A92.1990 requirements.
- Electroguard and fiberglass finished with white urethane paint over white gel coat.
- Non - lube bearings.
- 17 gallon integral hydraulic oil reservoir filled with oil and dual sight gauges.
- Master / slave hydraulic leveling system with upper control offering tilt for clean out and/or rescue.
- Ratchet style tie down straps and support for outer boom.
- 2 each, operator's and service manuals.
- ANSI A92.1990 data plate.
- Right hand single stick controls platform support with 180 degree platform rotator.
- Closed 24"x 30" platform with one step to the curbside.
- 24" x 30" platform liner with one step
- Platform capacity of 500 lbs.
- Platform cover, nylon /vinyl 24" X 30"
- Hydraulic articulating and extending jib pole and winch package for up to 1000lbs.
- Manual 2 speed for a Dodge chassis.
- Full body harness and lanyard (extra large)
- Aerial painted standard white
- Main A-frame outriggers with pivot feet located between the front of the body and the back of the cab.
- Level / slope indicator, attached to the curbside back body panel.
- Auxiliary independent narrow modified A-frame outriggers with outrigger legs at 10 degrees.
- Outrigger boom interlock system for main outriggers.
- Outrigger boom interlock system for auxiliary outriggers.
- Clutch / pump assembly to provide power to the aerial.

Quote Number: 010110-0

SERVICE BODY:

Brand FX Service Body model FB-84DLP:

Fiberglass service body for a cab and chassis with 84" CA and with dual rear wheels.
Length: 125-3/4", Width: 94", Height: 40", Compartment depth: 20"

FEATURES:

- FlexGlo compartment lighting along top and sides of compartment doors.
- Non-skid bin tops.
- Stainless steel door latches, steel hardware, and hinges.
- Double laminated doors.
- Vinyl coated stainless steel door cables.
- Exterior paint is a long lasting gelcoat.
- Superior weatherproofing is provided with factory installed continuous automotive bulb type door seals.
- All body wiring installed in a protective loom.
- Wheel well sections are separate from the side packs.
- Drip rail, rock guards, front panel, and rear plate are of aluminum construction.
- Floor is constructed of aluminum treadplate.

Lights:

- Side marker lights and reflectors installed per FMVSS #108.
- Flush mounted stop, tail, turn, and back up lights installed in the rear panel of the tailshelf per FMVSS #108.
- Lighted license plate bracket installed at the rear of the body.

STREETSIDE COMPARTMENTATION:

Full length hot stick shelf with drop down door at rear.

COMPARTMENT #1:

- Two (2) adjustable shelves each with adjustable dividers on 4" centers, and shelves evenly spaced.

COMPARTMENT # 2:

- Two (2) adjustable shelves each with adjustable dividers on 4" centers, and shelves evenly spaced.

COMPARTMENT #3:

- Open horizontal compartment.

COMPARTMENT #4:

- Two (2) adjustable shelves each with adjustable dividers on 4" centers and shelves evenly spaced.

CURBSIDE COMPARTMENTATION:

Compartment #1:

- Seven (7) locking swivel hooks spaced evenly in the compartment installed in the 2-3-2 position.

Compartment #2:

- Grip strut access step to load area.
- One stainless steel grab handle.

Compartment #3:

- Horizontal compartment with one adjustable shelf with dividers on 4" centers.

Compartment #4:

- Three (3) adjustable shelves each with adjustable dividers on 4" centers, and shelves spaced evenly apart.

MISCELLANEOUS EQUIPMENT

Four (4) polyurethane 18" x18" x 1" outrigger pad with a rope style handle.

Four outrigger pad carriers, one installed under each of the second vertical compartments and one under each of the rear compartments.

Two Buyers rubber wheel chocks with rope eyes 10" L x 6" H x 8" W.

Strobe system consisting of four (4) Ecco model 3810A amber, L.E.D. oval strobe lights. Two (2) installed in the front grille of the chassis and two (2) installed in the rear panel of the tailshelf. One (1) Ecco model 6750A strobe beacon post mounted on top of the streetside 1st vertical compartment towards the front. All strobes wired to a master switch located in the cab.

One (1) Ecco model SA901 backup alarm installed at the rear of the unit.

Alarm features a compact housing and rugged construction with optional decibel range of 82-107 db.

One (1) 5 LB, ABC rated, fire extinguisher installed at location determined at the pre paint inspection.

One (1) Triangle reflector kit. Shipped loose.

TAILSHELF

Tailshelf of 24" aluminum treadplate with storage and a drop down door on each side.

Tailshelf includes one pool type grab handle installed at rear curbside, and one EZ step mounted under the tailshelf on the curbside.

TOWING EQUIPMENT

One (1) ICC bumper with safety D-rings installed at the rear of the unit.

Buyers PH8, medium duty pintle hitch - 8 ton capacity.

Six prong trailer socket installed at the rear of the unit adjacent to the pintle hitch location.

MUDFLAPS

Mudflaps installed per state and federal regulations.

UNIT CERTIFICATION

Unit certification.

Chassis

2010 Dodge 5500 4x4 chassis.

84" cab to axle.

19,500 GVWR.

6 Speed automatic transmission.

6.7 liter diesel engine.

Power take off provision.

Cruise control.

Trailer brake controller.

Anti-spin differential rear axle.

160 amp alternator.

Engine block heater.

Goodyear 225/70R19.5F All Traction tires.

FOB: Springfield, IL

State and municipal sales taxes are to be added if applicable.

FET shall be added if applicable.