

Drake-Scruggs Equipment Inc.

Distributors of Truck and Utility Equipment

Home Office

2000 South Dirksen Parkway
P.O. Box 2549
Springfield, IL 62708-
(217) 753-3871
Fax (217) 753-2760

Branch Office

4101 W. Main Street
Grandview, MO 64030-
(816) 765-5525
Fax (816) 765-8522

****Call for current pricing****

Quote Number: 053309-0

AERIAL

VST-47-SI, Insulated 47'4" articulated, material handling, aerial platform lift, including the items listed.

- Standard platform capacity of 400 lbs (181kg).
- Fiberglass upper boom finished with white urethane paint over white gel coat. Boom is dielectric tested per ANSI A92.2-1990, Category C, 46-KV and below.
- Chassis insulation system (lower boom insert) with 12" insulation gap.
- Engine start /stop from platform and lower controls.
- Standard 46.25 inch pedestal with 17-gallon integral hydraulic oil reservoir with sight level gauge.
- Continuous rotation including,
- Six gpm open center hydraulic system operating at 3000 psi.
- One set of hydraulic tool outlets at platform with quick disconnects.
- Hydraulic platform rotator that rotates the platform 100 degrees from one side of the boom to 10 degrees past the end hung position.
- Manual platform tilt with hydraulic dampeners.
- Full pressure turret mounted lower controls with override.
- 12 volt emergency power.
- Jib and Winch with 1,000 lbs capacity.
- Non-lube bearings used at all pivot points.
- Upper boom cradle with ratchet type tie down strap.
- Tubular rubber platform support and lower boom cradle.
- Standard white urethane paint.
- Two operator's manuals and two service manuals.
- ANSI A92.2-1990 data plate.
- Right hand single stick control platform support.
- Closed 24x30 fiberglass platform, 1 step to curb side.
- 24" x 30" platform liner with one step.
- Platform cover, nylon /vinyl 24" X 30".
- Radio controlled chassis throttle control.
- Insulated jib pole extension and single line holder. 3"OD X 36".
- Full body harness and lanyard (extra large)
- Aerial painted standard white.
- Main A-frame outriggers with pivot feet located between the front of the body and the back of the cab.
- Auxiliary modified A-frame outriggers mounted between the back of the body and the tailshelf.
- PTO and gear pump to power the unit.

SERVICE BODY:

Brand FX Service Body model FB-84DLP:

Fiberglass service body for a cab and chassis with 84" CA and with dual rear wheels.

Length: 125-3/4", Width: 94", Height: 40", Compartment depth: 20"

FEATURES

- FlexGlo compartment lighting along top and sides of compartment doors.
- Non-skid bin tops.
- Stainless steel door latches, steel hardware, and hinges.
- Double laminated doors.
- Vinyl coated stainless steel door cables.
- Exterior paint is a long lasting gelcoat.
- Superior weatherproofing is provided with factory installed continuous automotive bulb type door seals.
- All body wiring installed in a protective loom.
- Wheel well sections are separate from the side packs.
- Drip rail, rock guards, front panel, and rear plate are of aluminum construction.
- Floor is constructed of aluminum treadplate.
- FlexGlo compartment lighting along top and sides of compartment doors.

Lights:

- Side marker lights and reflectors installed per FMVSS #108.
- Flush mounted stop, tail, turn, and back up lights installed in the rear panel of the tailshelf per FMVSS #108.
- Lighted license plate bracket installed at the rear of the body.

STREETSIDE COMPARTMENTATION:

Full length hot stick shelf with drop down door at rear.

COMPARTMENT #1:

- Two (2) adjustable shelves each with adjustable dividers on 4" centers, and shelves evenly spaced.

COMPARTMENT # 2:

- Two (2) adjustable shelves each with adjustable dividers on 4" centers, and shelves evenly spaced.

COMPARTMENT #3:

- Open horizontal compartment.

COMPARTMENT #4:

- Two (2) adjustable shelves each with adjustable dividers on 4" centers and shelves evenly spaced.

CURBSIDE COMPARTMENTATION:

Compartment #1:

- Seven (7) locking swivel hooks spaced evenly in the compartment installed in the 2-3-2 position.

Compartment #2:

- Grip strut access step to load area.
- One stainless steel grab handle.

Compartment #3:

- Horizontal compartment with one adjustable shelf with dividers on 4" centers.

Compartment #4:

- Three (3) adjustable shelves each with adjustable dividers on 4" centers, and shelves spaced evenly apart.

MISCELLANEOUS EQUIPMENT

Four (4) polyurethane 18" x18" x 1" outrigger pad with a rope style handle.

Four outrigger pad carriers, one installed under each of the second vertical compartments and one under each of the rear compartments.

Two Buyers rubber wheel chocks with rope eyes 10" L x 6" H x 8" W.

Strobe system consisting of four (4) Ecco model 3810A amber, L.E.D. oval strobe lights. Two (2) installed in the front grille of the chassis and two (2) installed in the rear panel of the tailshelf. One (1) Ecco model 6750A strobe beacon post mounted on top of the streetside 1st vertical compartment towards the front. All strobes wired to a master switch located in the cab.

One (1) Ecco model SA901 backup alarm installed at the rear of the unit.

Alarm features a compact housing and rugged construction with optional decibel range of 82-107 db.

One (1) 5 LB, ABC rated, fire extinguisher installed at location determined at the pre paint inspection.

One (1) Triangle reflector kit. Shipped loose.

TAILSHELF

Tailshelf of 24" aluminum treadplate with storage and a drop down door on each side.

Tailshelf includes one pool type grab handle installed at rear curbside, and one EZ step mounted under the tailshelf on the curbside.

TOWING EQUIPMENT

One (1) ICC bumper with safety D-rings installed at the rear of the unit.

Buyers PH8, medium duty pintle hitch - 8 ton capacity.

Six prong trailer socket installed at the rear of the unit adjacent to the pintle hitch location.

MUDFLAPS

Mudflaps installed per state and federal regulations.

UNIT CERTIFICATION

Unit certification.

FORD CHASSIS

2010 Ford F-550 4 X 4 cab and chassis with 84" CA and 19,500 GVWR.

- 6.4L V8 Diesel engine.
- 5 speed automatic transmission.
- XLT Trim Package.
- Medium Stone interior.
- Oxford White exterior.

FOB: Springfield, IL

State and municipal sales taxes are to be added if applicable.

FET shall be added if applicable.