

# Drake-Scruggs Equipment Inc.

Distributors of Truck and Utility Equipment

## Home Office

2000 South Dirksen Parkway  
P.O. Box 2549  
Springfield, IL 62708-  
(217) 753-3871  
Fax (217) 753-2760

## Branch Office

4101 W. Main Street  
Grandview, MO 64030-  
(816) 765-5525  
Fax (816) 765-8522

***\*Call for current pricing\****

**Quote Number: 093609-0**

## Aerial

Versalift VST-6000-I, Insulated 60'-1" telescopic aerial platform lift with a 65' working height. Standard Equipment:

- Platform mounted full pressure Unitrol single-stick control including safety trigger, emergency stop, and 180 degree hydraulic platform rotator with tilt for cleanout or rescue.
- Engine start/stop located at the platform and lower controls
- Continuous rotation shall include one electrical pass slip ring for the start/stop system.
- Open Center hydraulic system rated at six gallon per minute with a 2250 psi operating pressure.
- Side mounted telescopic upper boom allows low stowing of platform
- Chassis insulation system (fiberglass lower boom insert) shall include accommodations to bridge insulation gap for testing per ANSI A92.2 and also provides a 24 inch insulation gap.
- Non-lube bearings used throughout.
- One set of hydraulic tool outlets at the platform.
- A-frame outriggers with pivot feet attached to the sub-frame for torsional stability includes two control valves, selector valve located between the back of the cab and the front of the body.
- Tubular pedestal with an internal reservoir that has a 25 gallon capacity and dual sight gauges.
- Closed heavy duty one step 24 " x 48" x 42" fiberglass platform.
- Master/slave hydraulic leveling with upper and lower control to tilt for cleanout or rescue.
- Upper boom storage cradle with ratchet type tie down strap.
- Tubular rubber support supplied for the buckets resting position.
- White urethane paint.
- Two operator's manuals and two service manuals (in English) shipped loose with the unit.
- ANSI A92.2 data plate shall be installed on the pedestal of the completed unit.
- One set of hydraulic tool outlets at platform.
- 24" x 48" Vinyl/Nylon platform cover supplied with the platform.
- Platform capacity of 450 lbs with jib and winch installed, 600 lbs without jib and winch installed.
- Hydraulic articulating and extending jib pole and winch package for up to 1000 lbs (453kg) capacity.
- Standard pedestal (51 inches).
- Category B 69 KV dielectric certification.
- Chassis throttle control.
- Emergency 12V DC hydraulic system
- Standard start/stop.
- 5 pass collector ring assembly.
- Full body harness and lanyard (extra large) shipped loose with the unit.
- Auxiliary modified A-frame outriggers installed at the rear of the unit between the tailshelf and the body.
- Outrigger boom interlock system for main and auxiliary outriggers.
- 24" x 48" X 42" platform liner with a step.
- Hydraulic quick disconnects installed on tool circuit outlets at the platform.
- PTO and gear pump to power the unit

**Body:**

BrandFX model BFXB-150-48 W3 fiberglass service body for installation on a bare cab and chassis with dual rear wheels.

Length: 156"    Width: 94"    Height: 48"    Compartment Depth: 18"

**Standard Features:**

- Steel understructure.
- 3/16" aluminum treadplate floor.
- 3/16" smooth aluminum header panel, steel tail skirt.
- Standard white gel coat paint.
- Type 304 stainless steel slam latch, hardwire, and door hinges.
- Vinyl covered stainless steel doorstops.
- Non skid compartment tops.
- Full length aluminum drip rails.
- Aluminum rock guards.
- Automotive grade bubble gaskets.
- One piece molded doors.
- Flow through ventilation system.

**LIGHTS:**

- Flush mounted LED stop, tail, turn and back up lights installed in the rear of the tailshelf.
- Side marker lights and reflectors installed per FMVSS # 108.
- Lighted license plate bracket installed at the rear of the vehicle.

**Compartmentation Streetside:**

**Streetside Compartment 1 / Vertical:**

- Combination swivel hook in 2-3-2 configuration and installed as high as possible in the compartment.

**Streetside Compartment 2 / Vertical:**

- Four (4) adjustable divider shelves spaced evenly within the compartment, and with each shelf containing shelf dividers in every divider slot.

**Streetside Compartment 3 / Vertical:**

- Three (3) adjustable divider shelves spaced evenly within the compartment, and with each shelf containing shelf dividers in every divider slot.

**Streetside Compartment 4 / Horizontal:**

- One (1) divider shelf installed on the compartment bottom and all divider slots filled with shelf dividers.
- One (1) adjustable divider shelf mounted mid compartment, and with all divider slots filled with shelf dividers.

**Streetside Compartment 5 / Vertical:**

- Seven (7) Combination swivel material hooks installed in 2-3-2 position as high as possible in the compartment.

**Hotstick Shelf**

One (1) full length hotstick shelf on the streetside - plywood lined, and with a rear drop down door.

**Compartmentation Curbside:**

Curbside Compartment 1 / vertical:

- Seven (7) combination swivel material hooks installed in the 2-3-2 position as high as possible in the compartment.

Curbside Compartment 2 / Vertical:

- Four (4) adjustable divider shelves spaced evenly within the compartment, and with each shelf containing shelf dividers in every slot.

Curbside Compartment 3 / Vertical:

- Side access to the cargo area, including a grab handle on each side of the access, mounted on the outside of the body and with a grip strut access step located below the body access step.

Curbside Compartment 4 / Horizontal:

- One (1) divider shelf installed on the compartment bottom with shelf dividers in every slot.  
- One (1) adjustable divider shelf mounted mid compartment, with shelf dividers in every slot.

Curbside Compartment 5 / Vertical:

- Seven (7) combination swivel material hooks installed in the 2-3-2 position and mounted as high as possible in the compartment.

Flexglo rope style compartment lights installed along the inside and top of each compartment door, then wired to a switch panel in the chassis cab.

**Miscellaneous Equipment**

Level / slope indicator installed at rear and side of unit.

Two (2) outrigger pad carriers, one installed under the front vertical compartment on each side of the body.

1 (one) pool type grab handle installed at curbside of tailshelf near access step.

Four (4) flush mounted, oval, amber strobe lights - installed two (2) each side of the chassis grille, and two (2) installed at rear of vehicle.

Two (2) # 6710 A, amber LED strobe lights, post mounted to each side of the boom rest and wired to a switch installed in the chassis cab.

One (1) Ten pound, dry chemical, ABC rated fire extinguisher with cover installed near outriggers behind chassis cab.

One (1) Triangle reflector kit installed in chassis cab.

Four (4) Buyers rubber wheel chocks with rope eyes 10" L x 6" H x 8" W and stowed in each wheel chock holder.

Four (4) Polyurethane 18" x 18" x 1" outrigger pad with a rope style handle. Stowed in outrigger pad carriers (two per carrier)

**Tailshelf**

One (1) aluminum treadplate tailshelf 24" x 94" with an access step built into the curbside.

EZ access step under curbside rear of tailshelf

**Towing Equipment**

One (1) Buyers Manufacturing model PH20, rigid mount 20 ton capacity pintle hitch installed at the rear of the vehicle in conjunction with an ICC bumper / hitch plate combo that has a safety chain D-ring on each side of the pintle mounting area.

One (1) six prong trailer socket installed at the rear of the vehicle and adjacent to the pintle hitch location.

One (1) 96-8331 electric brake control installed in the cab and wired to the trailer socket.

**Mudflap**

Mudflaps installed per federal and state regulations.

**Certification**

Test and Certify the completed unit for stability, weight, and dielectrics.

**Chassis**

2010 Ford F750 Cab Chassis with the following features:

- 33,000 GVWR.
- 120" Cab to axle
- Cummins 6.7 L diesel engine - ISB, 280 HP @ 2400 RPM.
- Allison 3000 vocational 6-speed transmission with PTO provision.
- Engine block heater.
- 130 amp alternator.
- Left hand mounted 65 gallon steel tank.
- Tires; front Hankook 11R22.5H.
- Tires; rear Hankook 11R22.5H.
- Stainless steel west coast door mounted side mirrors with light heads, and heated.
- Heater, defroster, air conditioning.
- High back air-suspension driver seat with 2-man mid back toolbox passenger seat.
- AM/FM radio with clock.
- Chassis cab is painted standard white.
- XL trim package with cloth headliner, coat hooks, cloth sun visors with passenger mirror with a chrome grille and bumper.
- Front tow hooks.
- Air brakes
- Exterior color Oxford White.

***FOB: Springfield, IL***

***State and municipal sales taxes are to be added if applicable.***

***FET shall be added if applicable.***